

NPR

New Product Release



Release Date: 4-01-2017

SKB

Compact
Unit Heater

5kW to 10kW Models
for Large Spaces

Simple & Innovative Heating Solutions
for Making a Large Workshop/Garage
or Warehouse Space More Comfortable



SKB Compact Unit Heater

Compact Design

Permanently Lubricated Motor

High Efficiency Aluminum Fan

High Mass Steel Fin Heat Exchanger

Adjustable Louvers to Direct Air Flow

Universal Wall/Ceiling Bracket

Provided with Built-In Thermostat

*Prewired for Remote Wall Thermostat

High/Low Switch & Built-In Fan Delay
(Not available in 5KW Heater)

Power ON & Over-Temp Caution Lights

Patented Smart Limit Protection 

WARRANTY

3-Year Limited Warranty

NPR



New Product Release

Simple & Innovative Heating Solutions for Making a Large Workshop/Garage Warehouse Space More Comfortable

Comfort for Your Workers



Protection for Your Equipment



Advanced Features for Ease of Use & Durability



Compact-Profile Cabinet Design with Hanging Bracket –
Allows More Overhead Space for Increased Flexibility Of Installation

Spiral Steel Fin Heating Elements –
Provides Excellent Heat Transfer & Enhanced Durability

Adjustable Louvers – To Direct Airflow for Optimal Performance

Built-In Thermostat & High/Low Switch – For Fine-Tuning Temperature Control

Patented Smart Limit Protection – Manual Reset Type for Worry-Free Operation

***Prewired for Optional Wall Thermostat – Line Voltage or 24V Control**
Field Installation of the Optional “Transformer Relay” Required for 24V Thermostat

Ordering Information - single phase

MODEL	UPC	KW	PHASE	BTUH	VOLTS	AMPS	MOTOR HP	CFM	TEMP. RISE	AIR THROW	MAX. MOUNT	WT. (lbs.)	LIST PRICE
SKB2005-1-T-B	13413	5	17	1	208	24	9W	400	40°	16ft.	8ft.	30.5	595.00
*SKB2007-1-T-B	13414	7.5	25.6	1	208	36.1	16W	600	40°	20ft.	9ft.	45.0	942.00
*SKB2009-1-T-B	13415	9.2	31.4	1	208	44.2	25W	725	42°	24ft.	10ft.	45.0	1,090.00
SKB2405-1-T-B	13410	5	17	1	240/208	20.8/18	9W	400	40°	16ft.	8ft.	30.5	595.00
*SKB2407-1-T-B	13411	7.5	25.6	1	240/208	31.2/27	16W	600	40°	20ft.	9ft.	45.0	942.00
*SKB2410-1-T-B	13412	10	34.1	1	240/208	41.6/36.1	25W	725	44°	24ft.	10ft.	45.0	1,090.00

