

High Velocity Outdoor Rated Air Circulator WFO Series



Optional Misting Kit (Shown)



Model Code:

WFO -24
A B

A: Series
B: Fan Diameter
-24 = 24"
-30 = 30"



- 24" & 30" Commercial High Velocity Oscillating Air Circulator
- Outdoor Rated with Wall Mount
- Wall mounted to direct airflow
- 80 degree oscillating motion
- Optional Misting Kit Available
- Optional Fan-Speed-Controller
- 3-Speed Pull Chain Switch
- Totally Enclosed, Outdoor Rated Motor
- 3 Aerodynamically Balanced Blades
- Heavy Duty Steel Fan Guards
- Meets OSHA 1910.212(A)(5) Requirements
- 9 Ft, 120V Grounded Cord & GFCI Plug
- Scratch Resistant, Powder- Coated Finish
- UL Certified for USA & Canada
- 1-Year Limited Warranty

The King High Velocity Commercial Air Circulator

King Commercial High Velocity Outdoor Rated Oscillating Air Circulators are a powerful commercial-grade solution for cooling workshops, warehouses, factories, gyms and more. This oscillating fan motion distributes airflow in a 80 degree sweeping motion or disengage for manual desired hand positioning. The waterproof, totally enclosed motor is outdoor rated for wet locations and offers 3-speeds. Featuring 3 aerodynamically balanced aluminum blades for even, steady airflow and to provide maximum air and motor efficiency. The scratch resistant King green finish looks sharp and is easy to clean. Wall Mounted to direct the air flow where you need it most.

Ordering Information

MODEL NUMBER	UPC #093319	DESCRIPTION	CFM	WT. (lbs.)
WFO-24	33154	24" Outdoor Rated Oscillating Wall Mounted Air Circulator	7500/6200/4900	67.2
WFO-30	33155	30" Outdoor Rated Oscillating Wall Mounted Air Circulator	8200/6800/5300	73.3

Accessories

MODEL	UPC	DESCRIPTION	SHIP WEIGHT lbs
PFO-MISTKIT	33153	Add-On Accessory For Optional Misting Feature	0.5
FO-COVER-24	55376	24" Water Resistant Fan Cover	0.25
FO-COVER-30	55377	30" Water Resistant Fan Cover	0.25
FAN-SPEED-CONTROLLER	55378	Fan Motor Variable Speed Control Plug-In, 120V 3A Max	0.5



FAN-SPEED-CONTROLLER



FO-COVERS (Available in 24" & 30")

High Velocity Outdoor Rated Air Circulator WFO Series

WFO Series



Outdoor Rated
for Wet Locations

Water Resistant
Fan Cover
(Available in 24" & 30")

Oscillating Fan Motion Distributive
Airflow in a 80 Degree Sweep or
Disengage for Manual Desired
Hand Positioning

(3) Non-Corroding
Aluminum Blades
for Maximum Airflow

3-Speed Pull Chain
Switch Controls Air
Flow Output to
Match Your Needs

Optional Misting
Kit Available: Adds
a Fine Mist of Cool
Comfort to Hot
Environments

Wall Mount Bracket

9 Ft Grounded Three
Wire Conductor Cord
& GFCI Plug, 120V -
For Easy Portability
& Safety

Optional
PFO-Mistkit

